

SUPER STRIPPER
GEL EXPRESS
UNIVERSAL

EFFECTIVE ON ALL SURFACES:
WOOD, METAL, STONE, CEMENT, TILING, GLASS, ETC.

- Strips horizontal and vert cal surfaces back to original condition.
- Easily and thoroughly strips multiple layers of paints, varnishes, woodstains, glues, mastics (apart from two-component coatings and non-mineral render without damaging underlying surfaces.
- Does not run on vertical surfaces thanks to its gel texture.

	Ακρυλικό βερνίκι , βαφή, βερνίκι εμποτισμού στο ξύλο Acrylic varnish, paint, woodstain	Βερνίκι διαλύτου, βερνίκι εμποτισμού στο ξύλο Solvent-based varnish, woodstain	Βαφή διαλύτου Solvent-based paint
▶ 2 στρώσεις / 2 coats	3 min.	3 min.	5 min.
▶ Πολλές στρώσεις / Multi-layer	10 min.	15 min.	30 min.

APPLICATION

1 - Shake the container before use and wear gloves and safety goggles.
2 - Apply a thick, even coat with a paintbrush. A thick layer guarantees optimal results.
3 - Leave the stripper for 3 to 30 minutes depending on the number of coats to be stripped.
4 - Remove the softened coating using a stripping knife, scraper or steel wool.
5 - Use warm water (for easier removal) and a stiff brush (nylon or natural fibre) to rinse off the stripped surface.
6 - Leave to dry for 24 hours before applying a new finish.

Ideal conditions for application: between 15 and 30°C in mild, dry and settled weather. Do a patch test first. Do not use the stripper on plastic materials. Do not use in direct sunlight. Store in a cool place and do not keep in vehicles exposed to the sun.

V33 TIPS

- For best performance, sand layers with a coarse abrasive to facilitate penetration of the stripper.
- If possible, lay the material horizontally for better penetration of the stripper.
- If the result is patchy after the first application, reapply a thicker coat of stripper.
- On wood, use the stripping knife in the direction of the grain.
- Turn the stripper container upside down to use all of the product.
- This product can be used to clean wet and dry paintbrushes.





DANGER - Contains n-butyl Acetate. H225: Highly flammable liquid and vapour. H319: Causes serious eye irritation. H336: May cause drowsiness or dizziness. EUH066: Repeated exposure may cause skin dryness or cracking. P101: If medical advice is needed, have product container or label at hand. P102: Keep out of reach of children. P210: Keep away from heat, hot surfaces, sparks, open ames and other ignition sources. No smoking. P271: Use only outdoors or in a well-ventilated area. P501: Dispose of contents/container to a waste collection center (contact the local authority).